

NL) Productbeschrijving

MULTIFLEET MX is een high-performance minerale dieselmotorolie die speciaal is samengesteld om betrouwbare prestaties te leveren in een breed scala aan zware toepassingen. MIXEDFLEET MX is geschikt voor motoren met lage emissies (Euro II-, Euro III- en sommige Euro IV-motoren).

Toepassing

MULTIFLEET MX is aanbevolen voor alle moderne dieselmotoren van trucks, off-road-machines en andere zware toepassingen. Universeel gebruik, inclusief gemengde voertuigparken. Geschikt voor motoren met lage emissies met EGR (Euro II, III en sommige Euro IV). Voldoet aan de strenge eisen van vele Amerikaanse en Europese fabrikanten van dieselmotoren, en overtreft deze zelfs.

EN) Productdescription

MULTIFLEET MX is a high-performance mineral diesel engine oil formulated to deliver reliable performance in a broad range of heavy-duty applications. MIXEDFLEET MX is suitable for low-emission engines (Euro II, Euro III and some Euro IV engines).

Application

MULTIFLEET MX is recommended for all modern diesel engines of trucks, off-road equipment and other heavy-duty applications. Universal use, including mixed fleets. Suitable for low-emission diesel engines with EGR (Euro II, III and some Euro IV). Meets and exceeds the demanding requirements of many U.S. and European diesel engine manufacturers.

Specification

ACEA	A3/B3-10 – A3/B4-10
	E7-08#2
API	CI4 – CH4 – CG4 – CF
	SL
MB	228.3 – 229.1
MAN	M 3275
MTU	TYP 2
VOLVO	VDS-3
RENAULT	RLD – RDL-2
MACK	EO-M PLUS
ALLISON	C4
CUMMINS	CES 20076 – 7 – 8
CATERPILLAR	ECF-1A – ECF-2
GLOBAL/ JASO	DHD-1 – DH1
DETROIT DIESEL	93K215
DEUTZ	DQC-III-05

Articlnumbers

Bulk	212450
Drum 208 Lt	212451
Drum 60 Lt	212452
Can 20 Lt	212454

Typical Analytical Data

	Unity	Result
SAE	---	15W-40
Density	kg/m ³	888
Viscosity @ 40°C	mm ² /s	97
Viscosity @ 100°C	mm ² /s	13,8
Viscosityindex	---	144
Flashpoint	°C	220
Pourpoint	°C	-36
Total basenumber	mg KOH/g	10,5
Sulphated ashnumber	% mass	1,59

Tariccode	27101999
------------------	----------