

### NL) Productbeschrijving

Dit is een Low SAPS-smeermiddel met extra hoge prestaties dat is samengesteld op basis van speciaal geselecteerde basisoliën van hoge kwaliteit en een aangepast pakket additieven. De olie ondersteunt de uitzonderlijke prestaties van moderne zware motoren en biedt een volledige bescherming van het DPF (roetfilter).

### Toepassing

Aanbevolen voor de nieuwste 4-takt-dieselmotoren die zijn uitgerust met een DPF (roetfilter). Volledig achterwaarts compatibel: evenzeer geschikt voor oudere dieselmotoren met EGR (Euro III , IV). Overtreft de strenge eisen van de meeste fabrikanten van de V.S. en Europa.

Nabehandelingsbescherming: volledige bescherming voor het nabehandelingssysteem. Totale motorbescherming: uitstekende schone staat en duurzaamheid van de motor.

### EN) Productdescription

This is a new generation, Low SAPS, extra high performance lubricant formulated of specially selected, high-quality base oils and a customized additive package. It supports the exceptional performance of modern heavy-duty engines and offers complete protection of the DPF.

### Application

Recommended for the latest 4-stroke diesel engines fitted with DPF . Fully backwards compatible: equally suitable for older diesel engines with EGR (Euro III , IV). Exceeds the demanding requirements of most U.S. and European manufacturers.

Aftertreatment protection: full aftertreatment system protection.

Total engine protection: outstanding engine cleanliness and durability.

#### Specification

ACEA	E7-04 Issue 2
ACEA	E9-08 Issue 2
API	CJ-4/SM
MAN	M3575,M3477,M3271-1
Mbenz	MB 228.51

#### Articlnumbers

Bulk	212510
Drum 208 Lt	212511
Drum 60 Lt	212512
Can 20 Lt	212513

#### Typical Analytical Data

Unity	Result
SAE	10W-40
Density	861
Viscosity @ 40°C	96,2
Viscosity @ 100°C	14,2
Viscosityindex	152
Flashpoint	226
Pourpoint	-33
Total basenumber	8,9
Sulphated ashnumber	1,00

#### Tariccode

34031990