

NL) Productbeschrijving

STOU UN is een universele multigrade-olie voor motoren, transmissies, natte remmen en hydraulische systemen van landbouwtractoren.

Toepassing

STOU UN wordt aanbevolen voor de smering van dieselmotoren met of zonder turbocompressor, 4-takt-benzine- en LPG-motoren. Deze olie is geoptimaliseerd voor de smering van versnellingsbakken, achterassen, eindoverbrengingen, aftakassen, natte remmen, hydraulische systemen van landbouwtractoren en off-road-machines.

EN) Productdescription

STOU UN is an universal multigrade oil for engines, transmissions, wet brakes and hydraulic systems of agricultural tractors.

Application

STOU UN is recommended for the lubrication of charged and uncharged diesel engines, 4-stroke petrol and LPG engines. This oil is optimized for the lubrication of gearboxes, rear axles, final drives, power take-offs, wet brakes, hydraulic systems of agricultural tractors and off-road equipment.

Specification

ACEA	E3 – E2
API	GL4 – GL5
API	CF-4 – SF – CE
CCMC	D4
Ford ESN M2C	159 B/C – 121 C
	86 A/B – 134 C/D
MAN	271
MB	227.1
Massey M	1127 – 1135 – 1139
	1144
Allison	C4
Catterpillar	TO2
ZF TE-ML	06B – 07B
CASE NH	MAT 3525 – 3526

Articlnumbers

Drum 208 Lt	214001
Drum 60 Lt	214002
Can 20 Lt	214004
Carton 4x 5 Lt	---
Carton 12x 1 Lt	---

Typical Analytical Data

	Unity	Result
SAE	---	10W-40
Density	kg/m ³	875
Viscosity @ 40°C	mm ² /s	96
Viscosity @ 100°C	mm ² /s	14,4
Viscosityindex	---	150
Flashpoint	°C	220
Pourpoint	°C	-35
Total basenumber	g KOH/kg	10,7
Sulphated ashnumber	% mass	---

Tariccode	34031990
------------------	----------