

NL) Productbeschrijving

UTTO CD28 is een speciale olie bestemd voor automatische versnellingsbakken, hydraulische systemen, natte remmen, koppelvormers voor tractoren, vorkheftrucks en diverse off-road-machines. Let op: indien de fabrikant slechts één olie voor de smering van alle onderdelen inclusief de motor voorschrijft, wordt aan een S.T.O.U.-olie gerefereerd.

Toepassing

UTTO CD 28 voldoet aan de eisen van Volvo BM en kan worden gebruikt in transmissies, hefinrichtingen, achterassen en natte remmen van landbouwtractoren en off-road- machines en mobiele hydraulische systemen (kranen, verdeelblokken, stuurbevestiging).

EN) Productdescription

UTTO CD 28 is a special oil, intended for automatic transmissions, hydraulic systems, wet brakes, convertors for tractors, forklifts and different off-highway equipment. Remark : When the manufacturer prescribes only one oil for the lubrication of all parts, the engine included, he refers to a S.T.O.U. oil.

Application

UTTO CD 28 meets the requirements of Volvo BM, and can be used in transmissions, lifters, rear axles and wet brakes of agricultural tractors and off-highway equipment as well as moving hydraulic systems (cranes, junction box, power steering).

Specification

API	GL 4
CASE NH	MAT 3525 – 3505
CASE IH	MS 1206 – 1207 – 1210
VOLVO	WB 101
FORD NH	M2C 134C – D
FORD NH	FNHA-2-C-201.00
Allison	C4
John Deere	J20 C – D
ZF TE-MI	03E – 05F – 17E – 21F
Catterpillar	TO-2
MF	M1135 – 1143 – 1146

Articlnumbers

Drum 208 Lt	302281
Drum 60 Lt	302282
Can 20 Lt	302284
Carton 4x 5 Lt	---
Carton 12x 1 Lt	---

Typical Analytical Data

	Unity	Result
SAE Class	---	10W-30
ISO Class	---	68
Density	kg/m ³	885
Viscosity @ 40°C	mm ² /s	62,6
Viscosity @ 100°C	mm ² /s	10,7
Viscosityindex	---	162
Flashpoint	°C	212
Pourpoint	°C	-39
Total basenumber	g KOH/kg	6,4
Sulphated ashnumber	% mass	---

Tariccode	271019999
------------------	-----------