

NL) Productbeschrijving

Automatische-transmissievloeistof op synthetische basis die voldoet aan de vereisten van de General Motors Dexron VI-specificatie. Door de speciale samenstelling kan de vloeistof worden gebruikt in alle toepassingen waarvoor de oudere Dexron II- en Dexron III-vloeistoffen worden aanbevolen.

Toepassing

Deze ATF van hoge kwaliteit kan worden gebruikt in automatische transmissies met koppelmvormers van personenwagens, evenals in natte koppelingen en stuurbekekrachtigingseenheden.

EN) Productdescription

Automatic transmission fluid on synthetic base, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

Application

This high quality ATF can be used in automatic transmissions with torque convertors of passenger cars, as well as in wet clutches and power steering units.

Specification

MB	236.41
GM	Dexron VI
VOITH	55.6335.3X
Volvo	97342

Typical Analytical Data

	<i>Unity</i>	<i>Result</i>
SAE	---	--
Density	kg/m ³	847
Viscosity @ 40°C	mm ² /s	30
Viscosity @ 100°C	mm ² /s	6
Viscosityindex	---	151
Flashpoint	°C	--
Pourpoint	°C	-51
Brookfield viscosity @-40 C	mPas	13400
Sulphated ashnumber	% mass	---

Tariccode

34039900

Articlnumbers

Drum 208 Lt	303901
Drum 60 Lt	303902
Can 20 Lt	303904
Carton 4x 5 Lt	---
Carton 12x 1 Lt	---