

NL) Productbeschrijving

GEAROIL is een transmissieolie voor handgeschakelde transmissies met gemiddelde "extreme pressure" eigenschappen, speciaal ontwikkeld om corrosie van koperlegeringen te voorkomen.

Toepassing

GEAROIL is geschikt voor de smering van synchromesh-versnellingsbakken, tussenbakken, mechanische bedieningselementen van de besturing en de meeste achterassen (bepaalde achterassen moeten worden ingereden met een GL5-olie).

EN) Productdescription

GEAROIL is for mechanical transmissions with moderate "extreme pressure" characteristics and is specifically developed to avoid corrosion of copper alloys.

Application

GEAROIL is suitable for the lubrication of synchromesh gearboxes, transfer boxes, mechanical steering controls and most rear axles (certain rear axles should be run in with a GL5 oil).

Specification

API	GL 4
MIL	L-2105

Articlnumbers

Drum 208 Lt	300551
Drum 60 Lt	300552
Can 20 Lt	300554
Carton 4x 5 Lt	300555
Carton 12x 1 Lt	300558

Typical Analytical Data

	<i>Unity</i>	<i>Result</i>
SAE	---	80W-90
Density	kg/m ³	892
Viscosity @ 40°C	mm ² /s	148
Viscosity @ 100°C	mm ² /s	14,7
Viscosityindex	---	98
Flashpoint	°C	224
Pourpoint	°C	-30
Total basenumber	mg KOH/g	---
Sulphated ashnumber	% mass	---

Tariccode

27101999
