

### NL) Productbeschrijving

Dit is een volledig synthetische tandwielolie die wordt aanbevolen voor handgeschakelde transmissies van de meeste bedrijfswagens. De olie is aangepast aan de vereisten van synchromesh-transmissies, biedt een verbeterd schakelcomfort, verbeterde dunvloeibaarheid bij lage temperaturen en een langere levensduur.

### Toepassing

Dit product voldoet aan de vereisten van veel bedrijfswagen- en/of versnellingsbak fabrikanten, zoals Daf, IVECO, Eaton Europe (300.000 km of 3 jaar), Renault (conform B0032/2 annex 3) en Volvo.

### EN) Productdescription

This is a full-synthetic gear oil, which is recommended for the manual transmissions of most commercial vehicles. It is adapted to the requirements of synchromesh transmissions,procuring improved shift comfort,low temperature fluidity and longer service life.

### Application

This product meets the requirements of many commercial vehicle builders and/or gearbox manufacturers,including DAF,IVECO,Eaton Europe (300.000 km or 3 years),Renault (in accordance with B0032/2 Annex 3) and Volvo.

### Specification

API	GL 4 – MT-1
ZF TE-ML	01L – 02L – 08 – 16K
MAN	341 E3 – 341 Z4
Volvo	97307
MB	235.4

### Typical Analytical Data

	Unity	Result
SAE	---	75W-80
Density	kg/m <sup>3</sup>	865
Viscosity @ 40°C	mm <sup>2</sup> /s	57,9
Viscosity @ 100°C	mm <sup>2</sup> /s	9,75
Viscosityindex	---	154
Flashpoint	°C	234
Pourpoint	°C	-45
Total basenumber	mg KOH/g	---
Sulphated ashnumber	% mass	---

### Articlnumbers

Drum 208 Lt	302301
Drum 60 Lt	302302
Can 20 Lt	302304
Carton 4x 5 Lt	---
Carton 12x 1 Lt	---

<b>Tariccode</b>	34039900
------------------	----------